




CYGNUS 412

Fast Ethernet Media Converter

FEATURES

- ◆ CYGNUS 412 Fast Ethernet Media Converter which supports 10/100 Base-Tx to 100 Base-Fx media conversion
- ◆ One 10/100 Base-T Ethernet interface for connecting user device
- ◆ One 100 Base FX Fiber port with Bi-Di SC connector for connecting fiber line.
- ◆ Supports single mode and multimode fiber links (ordering time option)
- ◆ Driving range is up to 20 km on Single Mode Fiber (ordering option to support driving range upto 40 or 100 km) and 2 km on Multi-mode Fiber
- ◆ Bi-Di technology allows one fiber to be saved as compared to other Media Converters which use Duplex Fiber. Simultaneous 2-way communication between a pair of CYGNUS 412 units is possible using only one interconnecting fiber circuit between them.
- ◆ Supports 10/100Mbps operation with Auto Negotiation, Auto-sensing and Auto MDI/MDIX
- ◆ Compliant with IEEE 802.3 , 802.3u & 802.3x standards
- ◆ Power, Link, Activity and Speed LED indicators.
- ◆ Power supply: 5 VDC wall adaptor

TYPICAL APPLICATION



SPECIFICATIONS

FIBER OPTIC INTERFACE

Fiber type: Single Mode / Multi Mode (ordering option)
 Wave Length: 1310nm for multi mode optical interface
 1310/1550nm for single mode optical interface
 Range: Up to 20 km on single mode fiber (ordering option to support driving range upto 40 or 100 km) 2 km on multimode fiber (ordering option)
 Connector: Bi-directional SC (single fiber)

ETHERNET INTERFACE

Interface Compliance : IEEE 802.3 , 802.3u & 802.3x standards
 10/100 Base-Tx, Auto sensing
 Auto negotiation and Auto MDIX
 Speed: 10/100 Mbps
 Connector: RJ-45 Socket

INDICATORS

Power, Fiber Link/Act status, Ethernet Link/ACT and speed status

GENERAL

Size: 70mm (w) x 93mm (d) x 25mm (h)
 Power: 5 VDC external AC adaptor
 Operating temp: 0- 45° C
 Humidity: 0-85% RH, non condensing

ORDERING INFORMATION

Order Code: CYGNUS 412

Specifications and Features are subject to change without notice

Ref: 211108



CYGNUS MICROSYSTEMS (P) LIMITED

93, Phase II, IDA, Cherlapally, Hyderabad 500051, India
 Tel: +91 (40) 2726 1327

URL: www.cygnusmicro.com e-mail: mktg@cygnusmicro.com

ISO 9001 : 2015
 Registered